

CEE-BEE® A-953



SOLVENT DEGREASER AND CORROSION INHIBITOR REMOVER

CEE-BEE® A-953 is a thickened solvent based compound, used to effectively remove corrosion inhibiting compounds.

BENEFITS

- Slow evaporation
- Excellent solvency for removing corrosion inhibiting compounds, temporary coatings, greases, soils, and rubber residues from wheel hubs
- Safe for use on most painted surfaces when used as instructed
- Low vapour toxicity Safer than methyl ethyl ketone (MEK), toluene, xylenes, and halogenated solvents Ozone friendly
- Contains no phenolics, cyanides, nitrates, heavy metal salts, or hazardous solvents
- This product does not contain methylene chloride or halogenated solvents

PHYSICAL PROPERTIES

Appearance	Hazy liquid	Solubility	Non-soluble	Flammability	Combustible
Colour	Colourless	pH	N/A	Density	0.77 g/ml
Odor	Slight petroleum odour	Flash Point	N/A		

AVAILABLE FORMATS



19L

20CB953P

208L

20CB953D

1000L

20CB953T

APPROBATIONS

- ASSIGNED DOUGLAS DPM 6561-1
- BOEING D6-17487 REVISION "P"
- GOODRICH CORP. (WHEEL AND BRAKES)

USE PROCEDURES

1. Mix contents well before using.
2. Apply cleaner with mop, brush, or non-atomizing spray. To minimize streaking, begin at the bottom of the surface and work upward.
3. Allow cleaner to dwell for at least 5 minutes until soils are penetrated; then agitate surface with a brush or mop.
4. Rinse thoroughly with high pressure water, starting at the top of surface, and working downward. May require additional rinsing to avoid streaking and filming.

LEGISLATION

- WHMIS Regulated

SAFETY & HANDLING

- Refer to Safety Data Sheet (SDS) for additional information
- Dispose of container and its contents in compliance with all applicable regulations.
- Contains concentrated solvents. Avoid eye and skin contact. Use chemical resistant gloves and face shield or safety glasses, while handling and applying. ● Use with adequate ventilation. Do not use in confined areas. ● If ventilation is inadequate, use a NIOSH certified respirator which will protect against organic vapours, dusts and mists. ● Do not ingest. If accidental contact occurs, flush affected areas with water. If eye irritation persists, seek medical attention. If inhaled, seek fresh air. ● Store containers in a cool dry area. Open containers slowly to prevent any spewing of contents. Keep containers tightly sealed. Before using on plastic electrical insulation, or a painted surfaces that might be damaged, ensure that product will not degrade underlying substrates.

Information and recommendations regarding this product are presented in good faith. However no guarantees are associated with the data presented in this document, and no such guarantees should be interpreted from the information and expected results presented. We do not assume any liability for damage, loss or injury, direct or indirect, related to the use of this product.

Revised: 07 2020

P.2