

CEE-BEE® E-2060



HYDROGEN PEROXIDE ACTIVATED PAINT STRIPPER

CEE-BEE® E-2060 is a non-toxic, peroxide activated paint stripper designed for removing polyurethanes, epoxies and other paint systems.

BENEFITS

- Contains no halogenated solvents, phenols, or heavy metals
- Excellent at removing polyurethanes, epoxies and other paint systems
- Thixotropic: clings to vertical, inclined, and overhead surfaces
- Slow drying, allowing for maximum reaction time

PHYSICAL PROPERTIES

Appearance	Viscous liquid	Solubility	Approx.60%	Flammability	Non-flammable
Colour	Pink	pH	5.5-6	Density	1.05 g/ml
Odor	Mild Odour	Flash Point	N/A		

AVAILABLE FORMATS



19L

20CB206P

208L

20CB206D

1000L

20CB206T

APPROBATIONS

- AMS 1376B
- BOEING D6-17487, Rev. M (except magnesium immersion corrosion)
- THE BOEING COMPANY DPM 5549
- DOUGLAS CSD-1
- UNITED AIRLINES (CSM 5.01)
- VOUGHT 208-9-151

USE PROCEDURES

EQUIPEMENT:

- Use a high-pressure (5:1 or 10:1) air-activated pump equipped with a 1.3 cm (0.5 in) inside diameter high-pressure hose, and spray wand with a fan-type spray nozzle.
- Use a fan-type spray nozzle (such as 2508) for this application.
- Apply the stripper using a pump inlet pressure between 550–758 kPa (80–110 psi).
- For questions regarding suitable pumps or spray nozzles required for application, contact your DeaneCo representative.

APPLICATION:

1. Optimum performance is achieved when applying on surface temperatures: 24–30 °C (75–87 °F).
2. Surface to be stripped should be clean and completely dry.
3. Spray an even, medium coat of stripper, starting from the bottom of the aircraft and continue application upwards.
4. Keep the surface wet with stripper until paint buckling is observed.
5. Once paint is lifted, agitate the surface to remove the buckled paint.
6. Reapply stripper as required.
7. When all of the paint has been lifted, use a brush or squeegee to remove the loosened paint and residual stripper.
8. For optimal results, apply a mild alkaline cleaning solution such as SUPER BEE™ 210 to effectively remove paint and chemical stripper residues.
9. Thoroughly rinse the surface with water.

LEGISLATION

- WHMIS Regulated

SAFETY & HANDLING

- Refer to Safety Data Sheet (SDS) for additional information
- Dispose of container and its contents in compliance with all applicable regulations.

• Avoid skin or eye contact, may cause irritation. Safety glasses, face shield, chemical resistant gloves and personal protective equipment sufficient to avoid contact are recommended. • In case of accidental contact, flush affected areas thoroughly with water. If irritation persists, seek medical attention. • Do not ingest. • Use in well ventilated areas. • Do not mix with other paint strippers or materials containing chromium. • By-products and used stripper contents after use may be exothermic (releases heat); do not store used stripper and stripped coatings in closed containers. • Spent drums from E-2060 should be thoroughly rinsed before disposal. • If used stripper contents are placed back into an original E-2060 drum, drums must first be thoroughly rinsed, and sealed only with a vented cap.

Information and recommendations regarding this product are presented in good faith. However no guarantees are associated with the data presented in this document, and no such guarantees should be interpreted from the information and expected results presented. We do not assume any liability for damage, loss or injury, direct or indirect, related to the use of this product.

Revised: 07 2020

P.2