

CEE-BEE® R-256



ALKALINE ACTIVATED PAINT STRIPPER

CEE-BEE® R-256 is a viscous alkaline liquid compound, containing methylene chloride and phenols. Excellent at removing urethanes, epoxies, primers and enamels. Widely used on aircraft exteriors and for military applications.

BENEFITS

- Effective and economical
- Thixotropic: clings to vertical, inclined, and overhead surfaces
- Low odour
- Safe on most aircraft structural metals, including high strength and mild steels; cadmium, aluminum, magnesium and copper alloys
- Biodegradable surfactants

PHYSICAL PROPERTIES

Appearance	Viscous liquid	Solubility	Partially soluble	Flammability	Combustible
Colour	Opaque yellow	pH	9,5	Density	1.17 g/ml
Odor	Phenolic	Flash Point	74°C		

AVAILABLE FORMATS



19L

20CB256P

208L

20CB256D

1000L

20CB256T

APPROBATIONS

- AMS 1375
- BOEING D6-17487 REVISION "P"
- CSD-1, TYPE III
- MIL-R-81294D, TYPE I, CLASS 1 AND CLASS 3 (QPL)
- MIL-R-81294D, TYPE II, CLASS 1 AND CLASS 3 (QPL)
- MIL-R-81294D, TYPE IV CLASS 1 AND CLASS 3 (QPL)
- SIKORSKY AIRCRAFT SPECIFICATION SS 8786
- T.O.1-1-8

USE PROCEDURES

1. Before application, surface to be stripped should be dry and < 26 °C (80 °F), to achieve optimum stripping performance.
2. Apply a thin, uniform film of R-256, with non-atomizing spray, brush, or roller. Allow to dwell until coating is penetrated and loosened. For questions regarding a suitable applicator, contact your DeaneCo representative.
3. Agitate surface with a stiff bristle brush.
4. Reapply, if necessary. Once stripping/removal is complete, squeegee or scrape loosened coating and spent stripper from the surface for disposal.
5. Rinse surface with pressurized water.

LEGISLATION

- WHMIS Regulated

SAFETY & HANDLING

- Refer to Safety Data Sheet (SDS) for additional information
- Dispose of container and its contents in compliance with all applicable regulations.

WARNING! Contains chlorinated solvents and phenols. Rapidly absorbs through skin. Acute exposures may be fatal. ● Avoid eye and skin contact. Contact may not be immediately apparent. During application wear the following personal protective equipment: face shields and/or safety glasses, chemically resistant gloves, apron, pants, and boots. ● Apply with adequate ventilation. ● Do not ingest. ● In case of accidental contact, immediately flush affected areas with water for at least 30 minutes. Seek prompt medical attention. ● Open containers slowly to avoid accidental spewing of contents.

Information and recommendations regarding this product are presented in good faith. However no guarantees are associated with the data presented in this document, and no such guarantees should be interpreted from the information and expected results presented. We do not assume any liability for damage, loss or injury, direct or indirect, related to the use of this product.

Revised: 07 2020

P.2