

HONEY BEE™ 76



LIQUID CLEANER FOR AIRCRAFT TOILETS

HONEY BEE™ 76 is a concentrated cleaner specifically designed for removing gummy deposits that form in aircraft toilet systems.

BENEFITS

- Excellent at removing gummy deposits from aircraft toilets and components
- Resilient to hard water
- Safe on aluminum, high strength steels, magnesium and other common aircraft materials; including quality paints and acrylics
- Non-flammable

PHYSICAL PROPERTIES

Appearance	Liquid	Solubility	Water Soluble	Flammability	Non-flammable
Colour	Blue	pH	11.8-12.2	Density	1.06 g/ml
Odor	Pleasant odour	Flash Point	N/A		

AVAILABLE FORMATS



4L

20CBH76P

20L

20CBH76D

208L

20CBH76T

APPROBATIONS

- AIRBUS AMM Section – 38
- AIRBUS CML 14-001A, 11-001A
- AIR FRANCE CML 14-001A
- AMS 1476B
- AMS 1526A
- AMS 1530B
- AMS 1550B
- BOEING D6-17487, Rev. "H"
- BOEING AMM Section - 38
- DOUGLAS CSD-1
- MONOGRAM SANITATION
- SAS MTO-380414-2

USE PROCEDURES

Application to Toilet Systems.

1. Drain lavatory holding tanks and flush with clean water and deodorants, to remove any paper and waste contamination.
2. Pump HONEY BEE™ 76, undiluted or diluted up to 1 part water, from a service vehicle into the toilet holding tanks, 2.5 cm (1 in) above the toilet “flapper” valves. HONEY BEE™ 76 may also be poured directly into toilets.

Note: To prevent “over servicing” of lavatory holding tanks, the fluid level inside the toilet bowl should be monitored during the filling process.

3. Clean flush ring with an approved brush or tool, to remove debris. Mechanical removal is helpful since contact time with the flush ring is limited while the toilet flush motor is operating.
4. Allow cleaner to remain in the tank as long as possible and periodically flush toilets (hourly, if possible) to re-circulate the cleaner.
5. Drain the cleaner and thoroughly rinse holding tanks with water and lavatory deodorant before adding a fresh charge of deodorants.

Soak Application For Heavily Soiled Parts:

1. Charge soak tank with undiluted HONEY BEE™ 76, or diluted up to 1 part volume water.
2. To control tank odours, add 4 litres of HONEY BEE™ 50C Freshener Soak (Product # 25350) for every 1000 litres HONEY BEE™ 76 solution.
3. Allow parts to soak until soils have been penetrated. Mechanical agitation will reduce required soak time.
4. Remove parts from tank and rinse with water.

LEGISLATION

- WHMIS Regulated

SAFETY & HANDLING

- Refer to Safety Data Sheet (SDS) for additional information
- Dispose of container and its contents in compliance with all applicable regulations.
- Avoid skin or eye contact; may cause irritation. Safety glasses or face shield and chemically resistant gloves are recommended while handling. • In case of accidental contact, flush affected areas thoroughly with water. If irritation persists, seek medical attention.
- Do not ingest.

Information and recommendations regarding this product are presented in good faith. However no guarantees are associated with the data presented in this document, and no such guarantees should be interpreted from the information and expected results presented. We do not assume any liability for damage, loss or injury, direct or indirect, related to the use of this product.

Revised: 07 2020

P.2