

DE-9100

DEGREASER FOR TAR AND GREASE NATUR-SOLV 2

DE-9100 IS A DEGREASER FORMULATED TO REMOVE OILS, INKS, FATS, BITUMEN, AND WELL AS OTHER TENACIOUS SOILS FROM FERROUS AND NON-FERROUS ALLOYS. CAN BE USED IN SPRAYING OR IMMERSION SYSTEMS. RINSES QUICKLY AND EASILY.

BENEFITS

- Safe for metals
- Near neutral pH
- Concentrated formula for economical use
- Contains no petroleum solvents
- Contains natural citrus solvents to dissolve and eliminate heavy greases
- Versatile and compatible with a variety of cleaning operations, including pressure washing

PHYSICAL PROPERTIES

Appearance	Viscous Liquid	Solubility	Emulsifiable	Flammability	Combustible
Colour	Green opaque	pH	10.0	Density	0.985–0.995 g/mL
Odor	Light citrus	Flash point	ND / NA		

AVAILABLE FORMATS



20L

55DE9100P

208L

55DE9100D

1000L

55DE9100T

USE INSTRUCTIONS

1. Spray on the surfaces to be cleaned and allow to penetrate soiled surfaces for 10–30 minutes.
2. Dwell times will vary with surface conditions.
3. Rinse with a high pressure water jet.

Note: Application of DE-9100 on wet surfaces may dilute product and reduce its effectiveness. Use of hot water at high pressures will enhance product's efficiency. Natur-Solv can also be used by cold immersion. Mechanical agitation will enhance effectiveness. Immersion times will vary with types of soil and surface conditions.

Consult your Desco representative to optimize pump and dispensing systems.

SAFETY & HANDLING

- See the Safety Data Sheet for additional information
- Dispose of the contents / container in accordance with the applicable regulations

LEGISLATION

- Product regulated by WHMIS

Information and recommendations regarding this product are presented in good faith. However no guarantees are associated with the data presented in this document, and no such guarantees should be interpreted from the information and expected results presented. We do not assume any liability for damage, loss or injury, direct or indirect, related to the use of this product.

Revision: 07 2020